

DAFA Alu-Com Slim Line™

Product information sheet



The Alu-Com Slim Line glazing system makes it possible to optimise the energy rating of the windows, as the extremely small recession depth leaves room for better-insulated, sealed glazing units.

Application

The Alu-Com slim-line glazing system from DAFA makes it possible to incorporate triple glazing, for example, in a standard frame or casement rebate.

The glazing system comprises a 16 x 8 mm side-top glazing bead as well as a 16 x 18 mm bottom glazing bead.

The complete system including EPDM sealing strip requires a rebate depth of 11 mm from edge to pane.

Material



The Alu-Com Slim Line moulding profiles are made of aluminium alloy, designed to cope with the harsh Danish climate. The moulding profiles are held in place by an impact-resistant, durable mounting block. The moulding profile touching the pane is an extruded EPDM sealing strip and offers excellent weather resistance, held in place by the groove in the aluminium profile.

Benefits

- Leaves room for a better-insulated, sealed glazing unit, and thus a better energy rating
- The pane is kept securely in place - screw size 3 x 25mm, stainless steel
- Requires minimal maintenance
- Long service life
- Weatherproof
- Good ventilation and drainage option in the casement rebate
- Reduces the risk of dry rot, mould and punctures in sealed glazing units
- Can be used for all types of windows - new and old
- No nail holes


Delivery format

The aluminium profiles are supplied as 6-metre lengths of raw aluminium.



Drawing no. 1235774

Drawing no. 1235831



Drawing no. 15-810



Drawing no. 1235829



Drawing no. 1235775

Aluminium profile		EPDM sealing strip		Mounting block	
Aluminium alloy	6060F22	Type of rubber	EPDM	Type of plastic	PP
Density	2,70 kg / dm ³	Colour	Black	Casement extraction force	>50 kg / block
Hardness	75 Vickers	Hardness	60 ShA	Contents per pouch	300 pcs.

DAFA A/S (HQ)
Tel +45 8747 6666
www.dafa.dk

DAFA Deutschland GmbH
Tel +49 2761 94295-0
www.dafa-germany.de

DAFA Italia S.r.l.
Tel +39 0341 21141
www.dafa-italia.it

DAFA Sealing Technology (Tianjin) Co., Ltd.
Tel +86 10 8453 7428
www.dafachina.cn

LinkedIn
linkedin.dafa.dk

DAFA Sverige AB
Tel +46 431 258 30
www.dafa.se

DAFA US Inc.
Tel +1 312 810 6909
www.dafa-as.com

Interchemall Sp. z o.o.
Tel +48 22 739 04 00
www.interchemall.com.pl